

# GREENLANT® IN-040-GR

Recycled Polyethylene

## PRODUCT DESCRIPTION

**Greenlant® IN-040-GR** is made from carefully post-industrial/consumer product scrap. This rHDPE is designed for multipurpose of injection molding containers, crates and other applications such as chemical container caps.

**Product description:**

Green-color High Density Polyethylene

**Pellet size:**

3 mm – 4 mm strained cut

## STORAGE

The product should be stored in dry conditions at temperatures below 40 °C and protected from UV-light. Improper storage can initiate degradation, which results in odour generation and colour changes and can have negative effects on the physical properties of this product.

## PRODUCT TECHNICAL PROPERTIES

PROPERTIES	VALUE	UNIT
<b>Melt Flow Index</b> TS EN ISO 1133-1 2012 23°C-50%, 190°C 5Kg 5min. Preheating	4.0	g/ 10min
<b>Density</b>	0.950	g/ cm <sup>3</sup>
<b>Melting Range</b>	190	°C

## DISCLAIMER

**ATALANT** make no warranties which extend beyond the description contained herein. Nothing herein shall constitute any warranty of merchantability or fitness for a particular purpose.

It is the customer responsibility to inspect and test our products in order to satisfy itself as to the suitability of the products for the customer's particular purpose. The customer is responsible for the appropriate, safe and legal use, processing and handling of our products.

**ATALANT EUROPE**

[www.atalant.com](http://www.atalant.com)

Check our customer area or contact  
our commercial agents for more info

